


# Submersible Aerator





# **■ PERFORMANCE CURVE**



# ■ SPECIFICATION

Туре	Phase	Start Method	Voltage	Power		Caliber		Pole	Max. Water Depth	Air Flow Rate- Water Depth 50 / 60 Hz	No.of Outlets	Weight	Solid Passage
TYPE	PH		VOLT	HP	KW	Inch	mm	P	M	M³/hr		KG	mm
AJ-332	3Ø	Direct	220/380	3	2.2	2"	50	4P	3.6	39 / 38	8	126	15
AJ-352	3Ø	Direct	220/380	5	3.7	2"	50	4P	4.0	55 / 60	8	128	15



The real installation



Industry wastewater aeration treatment



# Submersible Aerator



#### APPLICATION

Industrial wastewater aeration treatment, animal husbandry sewage water aeration treatment, general sewer aeration engineering, aeration tank of the active slurry treatment in the plant, aeration of various industries and the apparatus of mixing wastewater treatment.


#### **■ CONVECTION PATTERN**

#### **Main Convection**


Convection made by rising bubbles.( The minimum distance that must be provided between each aerator.)


#### **Subsidiary Convection**

The maximum covection that can keep solids subsidiary pended to prevent sedimentation of solids.



#### ■ INSTALLATION CONSULTATION





A Circle Tank

A Rectangular Tank

(L:W=2:1)

(L:W=1.5:1)

### ■ STRUCTURAL DRAWING



#### ■ MATERIAL AND STANDARD TABLE

Caliber				50mm				
Coating				Ероху				
	Ter	npe	rature	0°C~40°C (32°F~104°F)				
Liquid	Ap	plica	ation	Water treatment, plants, pond aerations, sewage, treatment, aeration, fish farming.				
	The	e lo	west depth	<b>▽30 M</b>				
	Stru	lm	peller	Semi-open				
	Structure	Se	al	Dual Mechanical Seal				
		Up	per Cover	FC-200				
	Material	Вє	aring	Heavy-duty bearing				
		lm	peller	SCS13				
Pu		Vo	lute Casing	FC-200				
		Suc	ction Casing Cover	FCD-450				
Pump		Gι	ıide Vane	FCD-450				
		Sι	ction Plate	SCS13				
		Вс	ttom Plate	FCD-450				
		Seal	Lubricant	ISO VG. #32				
			Motor Side	Carbon / Ceramic				
			Pump Side	Silicon Carbide / Silicon Carbide				
			Inner Protector	Percipence Instrument of seal leakage				
	Туре			Submersible dry type				
	Ins	ulat	ion class	F class (155°C)				
Motor	Inn	er p	protector	Auto Reset Motor Protector				
	3	Ca	sing	FC-200				
	Material	Ma	ain Shaft	SUS-410/SUS420				
		Ca	ıble	Standard VCT / Optional				

<sup>\*</sup>Spare parts and material of pump could be made by request.

